

## POLLYTEX PES BLACKBACK SUB/UV MATT 240 gsm

100% polyester woven backdrops fabric

### APPLICATIONS:

Backdrops, Pop-up, Frame, Exhibition, Display systems

### MATERIAL DETAILS:

PROPERTIES	TYPICAL VALUE	TEST STANDARD
Material	100% polyester	DIN 60001,ASTM D7641
Weight	240±5%/sq.m;7.0±5%/sq.yd	ISO536
Thickness	290±30	ISO534
Opacity	95-100	ISO2471
Whiteness	145±10	ISO11475
Color	L*: 91±2.0 a*: 5.0±2.0 b*: -13.0±2.0	
Shrinkage	-2%	200°C , 45s
Yarn	150D*2x150D*2 denier	DIN EN 2060,ASTM D1907
Flame Resistance	DIN 4102-1-B1,NFPA 701	DIN 4102-1-B1,NFPA 701 Test1
Recommend Fixation Temperature	190-200°C, 45s	
Yellowing Temperature	≥210°C	SUPRKC REX-C400,30s

### INK SUPPORT:

Dye Direct	Dye Transfer	UV
✓	✓	✓

### PRODUCTION DETAILS:

WIDTH:	Max 320 cm	Standard: DIN EN ISO 3759,ASTM D751-2006
LENGTH:	50 m	Standard: DIN EN ISO 3759,ASTM D751-2006

### NOTE:

The product should be stored in the original packaging for protection.

It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources.

Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH;

Under this condition, the product shelf life is 1 year.