

DTEC BANNER PLUS FRONTLIT MATT 18X18 510 GSM

Product Specification:

| ITEM | DATA | UNIT | TEST METHOD |
|-----------------------|-----------------------------------------|------------------|-----------------------------|
| Fabric | High tenacity yarns 100% PES (1000D) | | DIN EN ISO 2060 |
| Construction | Weaving 18*18 | inch | DIN 60001 |
| Total weight | 510 | g/m ² | DIN 53352 BS 3424 method 5A |
| Weight of fabric | 158 | g/m ² | DIN 53352 BS 3424 method 5B |
| Weight of pvc coating | 352 | g/m ² | DIN 53352 BS 3424 method 5B |
| Tensile strength | Warp : 2150 | N/5cm | DIN 53354 BS 3424 method 6A |
| | Weft : 1850 | | |
| Tearing strength | Warp : 280 | N | DIN 53356 BS 3424 method 7A |
| | Weft : 220 | | |
| Adhesion | 80 | N/5cm | DIN 53357 BS 3425 method 9B |
| Suitable temperature | -20 / +70 | °C | DIN 53372 BS 3424 method 10 |
| Flame retardancy | No | | |
| Lacquering | No | | |

The indexes above are on average, so there will be ±5% tolerance of actual indexes.