

# DTEC BANNER PLUS FRONTLIT WHITE/BLACK MATT 450 gsm

coated frontlit 450gsm 1000\*1000 18\*18 black back

## MATERIAL DETAILS:

ITEM	DATA	UNIT TEST	METHOD
<b>Fabric</b>	High tenacity yarns 100%PES(1000D)		DIN EN ISO2060
<b>Construction</b>	Weaving 18*18	inch	DIN60001
<b>Total weight</b>	450	g/sq.m	DIN53352 BS3424 method5A
<b>Weight of fabric</b>	240	g/sq.m	DIN53352 BS3424 method5B
<b>Weight of pvc coating</b>	210	g/sq.m	DIN53352 BS3424 method5B
<b>Tensile strength</b>	Warp : 2300	N/5cm	DIN53354 BS3424 method6A
	Weft : 1900		
<b>Tearing strength</b>	Warp : 240	N	DIN53356 BS3424 method7A
	Weft : 200		
<b>Adhesion</b>	80	N/5cm	DIN53357 BS3425 method9B
<b>Suitable temperature</b>	-20 -----+70	°C	DIN 53372 BS3424 method10
<b>Flame retardancy</b>		No	
<b>Lacquering</b>		No	

The data above are on average, so there will be  $\pm 5\%$  tolerance.