

## DTEC MURAL DECO TEX SA MATT

### Product description:

- Film: 150d\*150d 115gsm woven Polyester
- Color: White
- Surface: Matt

### Application:

- Applying on the glossy smooth surfaces, eggshell paints etc walls.

### Printing method:

- Compatible with Solvent Ink, Eco-solvent, Latex, and UV Curable Inks

### Technical data:

CHARACTERISTIC	TEST METHOD	AVERAGE VALUES
Film Weight	ISO 4591:1992	150d*150d 115gsm woven Polyester
Adhesive type		High-tack and 100% Removable Glue, Repositionable
Release paper		160 gsm Double Sides PE-Coated Silicon Paper
Dimensional stability	FINAT TM14	Adhered to steel, 0.2mm in cross direction, in length 0.50mm max.
Temperature resistance		Adhered to aluminum. -20°C to +100°C, no variation
Seawater resistance	DIN 50021	Adhered to glass, after 48h/23°C no variation
Adhesive power	FINAT TM1	After 24h, stainless steel 11-15N/25mm
All of the weight of the materials		340gsm
Thickness of all the material		330microns
Shelf life		1 year
Storage		One year out of direct sunlight at 23°C and 50% humidity
Application temperature		Min.+10°C
Weathering		2 year
<p>Attention:</p> <p>After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination, which could affect the adhesion of the material.</p> <p>The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.</p>		