

## MAGNETO STEEL PET WHITE MATT PET SOL/UV/LX

### FEATURES AND ADVANTAGES:

- White matte PET steel film, compatible for (eco) solvent and Latex printing.
- Working as magnetism principle on magnets, easy to apply, remove and change, without residue
- Without demagnetized, anti-rust
- Premium PET base, good weather resistance, excellent for durable indoor display, big size is available

### MAGNETIC DATA:

Lifting Weight:  $\geq 3.5$  (g/cm<sup>2</sup>)

\*Condition: the standard test tool is isotropic rubber magnet 0.7mm (holding strength is about 40g/cm<sup>2</sup>), test equipment is Tensile Strength Tester.

### MATERIAL DETAILS:

PROPERTIES	METRIC	TEST STANDARD
Total thickness	180 $\mu$ m (+/-20)	N/A
Finished Material Weight	340g/sqm (+/-20)	N/A
Whiteness	[80,90]	N/A
Opacity	100%	N/A
Width [mm]	0,914/1070/1270/1370/1524/1626	N/A
Standard Length [m]	30/50m	N/A
Water resistance	Medium - High	N/A

### PROCESS AND STORAGE:

- Working condition: temperature 15°C to 30°C, and relative humidity 30% to 60%.
- Application condition: temperature change is within 30°C daily, relative humidity change is within 30%.
- Storage condition: closed preserve avoiding sunlight, temperature 10°C to 35°C, relative humidity 20% to 70%
- Shelf life: 12 months under storage condition. Unfinished material should be seal-packed, and used up within one month.

### PRINTING INDEX:

- compatible
- Δ testing required
- × not compatible

(ECO) SOLVENT	UV CURABLE	LATEX	DYE/PIGMENT	OFFSET/FLEXO	SCREEN PRINT	TONER BASED
○	Δ	○	×	○	○	Δ

NOTE: All mentioned data above are average of test result and should not be used for the purpose of lawsuit or warranty. This information should only be used as a guide and buyers shall independently test and determine products suitability