

DTEC ROLL UP ECONOMY PET SATIN GREY BACK

Description:

Ingredient: PVC/PET/PVC

Width: 0.914/1.27/1.52m

Features:

Perfect color reproduction with stable ink absorption and faster drying ability.

UV resistance, high tearing strength, suitable for roll up banner and X display rack.

Good flatness, no curling.

Application:

Widely used in commercial sign, exhibition, sports, election campaign, etc. The product is mainly suitable for digital inkjet printing and other printing method with Eco-solvent ink, HP Latex and UV.

Technical Data:

Testing condition: Indoor temperature $23\pm 2^{\circ}\text{C}$, Relative humidity $50\pm 5\%$

Test Term	Unit	Test Method	Average
Thickness	micron	GB/T6672-2001	250-10
Weight-finished product	g/m^2	GB/T4669	350-20
Tensile strength at MD	N/5cm	GB/T1040	≥ 700
Tensile strength at CD	N/5cm	GB/T1040	≥ 700
Applicable Temperature	$^{\circ}\text{C}$		-10~+45

Storage Condition:

All products always need to be stored in their original packing and with the original protection materials, preferably stored hermetically and vertically, do not expose to direct sunlight or heat sources. In order to avoid loss of quality, Products should also be stored in suitable conditions, that is at a temperature of $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and a relative humidity of $50 \pm 15\%$. Under these conditions, products can be stored up to one year.

Production and Application Environment:

Production environment: temperature of $25 \pm 5^{\circ}\text{C}$, relative humidity of $50\% \pm 10\%$, clean dust-free environment without suspended matter; Please move the materials to the printing environment 24 hours before printing. Printing test before use. Printing ink temperature of $18^{\circ}\text{C} - 28^{\circ}\text{C}$. Equipment preheating temperature of 30°C .

Application environment: temperature of 18°C to 28°C , relative humidity of $50\% \pm 15\%$

Warranty Condition:

1. One year service life: stored in suitable conditions, preferably use within 6 months.
2. One year prosecution period: from the product manufacture date, no-acceptance for overdue product.

Important Remark:

The information mentioned in this product data sheet is based upon tests that were executed, and that we consider to be reliable. Advise to use the same batch. Please evaluate on the project environment in advance to confirm the products suitability.