

## ImagePerfect<sup>™</sup> 2810-103 Clear Gloss Polymeric Laminate (FR)

ImagePerfect™ 2810-103 is a polymeric laminate with a permanent advanced acrylic adhesive that has been specifically designed for protecting digital prints.

ImagePerfect™ 2810-103 is a polymeric laminate incorporating specific polymeric, non-migrating plasticizers and UV stabilizers which ensure maximum light fastness and excellent outdoor durability. It is intended for many flat and slightly curved applications, such as markings and decorations, window graphics and vehicle graphics. This laminate can be used on IP 2553 Plus, IP 2553PA Plus, IP 2554 Plus, IP 2556 Plus and IP 2556PA Plus.

Specifications	
Description	Polymeric laminate
Colour	Clear gloss
Thickness	70mym
Weight	N/A
Adhesive	Advanced acrylic, permanent
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 135g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	7 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

<sup>@</sup> May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom



## ImagePerfect<sup>™</sup> 2810-202 Clear Matt Polymeric Laminate (FR)

ImagePerfect™ 2810-202 is a polymeric laminate with a permanent advanced acrylic adhesive that has been specifically designed for protecting digital prints.

ImagePerfect™ 2810-202 is a polymeric laminate incorporating specific polymeric, non-migrating plasticizers and UV stabilizers which ensure maximum light fastness and excellent outdoor durability. It is intended for many flat and slightly curved applications, such as markings and decorations, window graphics and vehicle graphics. This laminate can be used on IP 2553 Plus, IP 2553PA Plus, IP 2554 Plus, IP 2556 Plus and IP 2556PA Plus.

Specifications	
Description	Polymeric laminate
Colour	Clear matt
Thickness	70mym
Weight	N/A
Adhesive	Advanced acrylic, permanent
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 135g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	7 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

<sup>@</sup> May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom