

ImagePerfect[™] 2810-105 Clear Gloss 2D Wrap Laminate (FR)

ImagePerfect™ 2810-105 is a match-component vinyl laminate to be used in conjunction with ImagePerfect™ 2578PA 2D Wrap and IP 2578PA 2D Wrap SuperGlide, for use in fleet and vehicle applications with 2D, single-step recesses.

ImagePerfect™ 2810-105 is high-end, supersoft laminate, incorporating a special 50mym film that is to be used in conjunction with ImagePerfect™ 2578PA 2D Wrap and IP 2578PA 2D Wrap SuperGlide, for use in fleet and vehicle applications with 2D, single-step recesses. This special laminate will provide high levels of flexibility and conformability in application and high levels of clarity in use.

Specifications	
Description	Long-term supersoft laminate
Colour	Clear gloss
Thickness	50mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

[@] May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom



ImagePerfect[™] 2810-205 Clear Matt 2D Wrap Laminate (FR)

ImagePerfect™ 2810-205 is a match-component vinyl laminate to be used in conjunction with ImagePerfect™ 2578PA 2D Wrap and IP 2578PA 2D Wrap SuperGlide, for use in fleet and vehicle applications with 2D, single-step recesses.

ImagePerfect™ 2810-205 is high-end, supersoft laminate, incorporating a special 50mym film that is to be used in conjunction with ImagePerfect™ 2578PA 2D Wrap and IP 2578PA 2D Wrap SuperGlide, for use in fleet and vehicle applications with 2D, single-step recesses. This special laminate will provide high levels of flexibility and conformability in application and high levels of clarity in use.

Specifications	
Description	Long-term supersoft laminate
Colour	Clear matt
Thickness	50mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

[©] August 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom